

## HIGH TACK ADHESIVE MS5 WHITE 290 ML

Version 2.0      Revision Date: 29.11.2019      SDS Number: 2226347-00002      Date of last issue: 19.11.2018  
Date of first issue: 21.11.2017

---

**Section 1: Identification**

Product name : HIGH TACK ADHESIVE MS5 WHITE 290 ML

Product code : 0892 329 101

**Manufacturer or supplier's details**

Company : Wurth NewZealand Ltd

Address : 99 McLaughlins Road  
Wiri, Auckland 2104

Telephone : +64 9 262 3040

Emergency telephone number : 0800 764 766

E-mail address : prodsafe@wuerth.com

Telefax : +64 9 262 3030

**Recommended use of the chemical and restrictions on use**

Recommended use : Filler  
Construction material

---

**Section 2: Hazard identification****GHS Classification**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards which do not result in classification**

None known.

---

**Section 3: Composition/information on ingredients**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
trimethoxyvinylsilane	2768-02-7	< 10

---

**Section 4: First-aid measures**

If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.

**HIGH TACK ADHESIVE MS5 WHITE 290 ML**

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2018
2.0	29.11.2019	2226347-00002	Date of first issue: 21.11.2017

---

- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.
- 

**Section 5: Fire-fighting measures**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.
- 

**Section 6: Accidental release measures**

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.
-

## HIGH TACK ADHESIVE MS5 WHITE 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2018
2.0	29.11.2019	2226347-00002	Date of first issue: 21.11.2017

---

Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### Section 7: Handling and storage

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from water.  
Protect from moisture.  
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

Conditions for safe storage : Keep in properly labelled containers.  
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

Recommended storage temperature : 10 - 35 °C

## HIGH TACK ADHESIVE MS5 WHITE 290 ML

Version 2.0      Revision Date: 29.11.2019      SDS Number: 2226347-00002      Date of last issue: 19.11.2018  
 Date of first issue: 21.11.2017

### Section 8: Exposure controls/personal protection

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methanol	67-56-1	WES-TWA	200 ppm 262 mg/m <sup>3</sup>	NZ OEL
	Further information: Exposure can also be estimated by biological monitoring, Skin absorption			
		WES-STEL	250 ppm 328 mg/m <sup>3</sup>	NZ OEL
	Further information: Exposure can also be estimated by biological monitoring, Skin absorption			
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Ensure adequate ventilation, especially in confined areas.  
 Minimize workplace exposure concentrations.

#### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
 Safety glasses  
 Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.  
 Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Skin and body protection : Skin should be washed after contact.

### Section 9: Physical and chemical properties

Appearance : paste

Colour : white

## HIGH TACK ADHESIVE MS5 WHITE 290 ML

Version 2.0      Revision Date: 29.11.2019      SDS Number: 2226347-00002      Date of last issue: 19.11.2018  
Date of first issue: 21.11.2017

---

Odour : slight

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : > 100 °C  
Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : 20,000 - 35,000 mPa.s ( 20 °C)  
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

## HIGH TACK ADHESIVE MS5 WHITE 290 ML

Version 2.0      Revision Date: 29.11.2019      SDS Number: 2226347-00002      Date of last issue: 19.11.2018  
Date of first issue: 21.11.2017

---

Particle size : Not applicable

---

**Section 10: Stability and reactivity**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed upon contact with water or humid air.

Conditions to avoid : Exposure to moisture

Incompatible materials : Oxidizing agents  
Water

**Hazardous decomposition products**

Contact with water or humid air : Methanol

---

**Section 11: Toxicological information**

Exposure routes : Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

**Components:****trimethoxyvinylsilane:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.8 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

---







## HIGH TACK ADHESIVE MS5 WHITE 290 ML

Version 2.0      Revision Date: 29.11.2019      SDS Number: 2226347-00002      Date of last issue: 19.11.2018  
Date of first issue: 21.11.2017

---

**Section 12: Ecological information****Ecotoxicity****Components:****trimethoxyvinylsilane:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 191 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 168.7 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 957 mg/l  
Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): > 957 mg/l  
Exposure time: 72 h

**Persistence and degradability****Components:****trimethoxyvinylsilane:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 51 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**Section 13: Disposal considerations****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

**Section 14: Transport information****International Regulations**

UNRTDG

---

## HIGH TACK ADHESIVE MS5 WHITE 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2018
2.0	29.11.2019	2226347-00002	Date of first issue: 21.11.2017

---

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****NZS 5433**

Not regulated as a dangerous good

---

**Section 15: Regulatory information****Safety, health and environmental regulations/legislation specific for the substance or mixture****HSNO Approval Number**

HSR002544 Construction Products Subsidiary Hazard Group Standard 2017

**HSW Controls**

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

**The components of this product are reported in the following inventories:**

NZIoC : All ingredients listed or exempt.

---

**Section 16: Other information****Further information**

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average

---

## HIGH TACK ADHESIVE MS5 WHITE 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2018
2.0	29.11.2019	2226347-00002	Date of first issue: 21.11.2017

---

NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

NZ / EN